AMENDMENT TO CLAIMS

In the claims:

Please cancel claims 1-53.

Please enter the following new claims:

1.-53. (Cancelled.)

54. (New) A surgical instrument for applying high frequency electrical energy to tissue at a target site comprising:

a shaft having a proximal end and a distal end;

an electrode terminal having an active electrode surface at or near the distal end of the shaft, the active electrode surface comprising a hemispherical geometry;

an electrode support that holds the electrode terminal; and

a connector extending from the electrode terminal to the proximal end of the shaft.

- 55. (New) The surgical instrument of claim 54 further comprising a return electrode positioned on the shaft proximal to the electrode terminal.
- 56. (New) The surgical instrument of claim 54 wherein the return electrode is a substantially annular band positioned proximal to the electrode terminal.
- 57. (New) The surgical instrument of claim 54 wherein a distal portion of the shaft is bent.
- 58. (New) The surgical instrument of claim 57 wherein a distal portion includes a bend of 10-30 degrees.

Philip E. EGGERS et al.

Application No.: To be Assigned

Page 3

59. (New) The surgical instrument of claim 54 wherein the electrode terminal has a tissue treatment surface adapted to minimize dissociation and breakdown of collagen fibers in the tissue and to minimize ablation of tissue surrounding the collagen fibers

- 60. (New) The surgical instrument of claim 56 wherein the tissue treatment surfaces of the electrode terminal has a surface area less than about 1 mm².
- 61. (New) The surgical instrument of claim 54 wherein said electrode support comprises an inorganic material.
- 62. (New) The surgical instrument of claim 61 wherein said inorganic material is glass.
- 63. (New) The surgical instrument of claim 61 wherein said inorganic material comprises a ceramic.
- 64. (New) The surgical instrument of claim 63 wherein said inorganic material further comprises glass.
- 65. (New) A surgical instrument for applying high frequency electrical energy to tissue at a target site comprising:
 - a shaft having a proximal end and a distal end;
 - a hemispherical-shaped electrode terminal;
 - an annular return electrode spaced proximally from said electrode terminal; and
 - a connector extending from the electrode terminal to the proximal end of the shaft.

Philip E. EGGERS et al.

Application No.: To be Assigned

Page 4

66. (New) The surgical instrument of claim 65 further comprising an electrode support configured to hold the electrode terminal, said electrode support being non-electrically conducting.